2 August 1956

BUBJECT:	Visit to	25
1. T in 27 July 1956	ne and Place of Meeting: The meeting was held on	2 <u>!</u> 2!
2. <u>At</u> i	tendance:	25
3. Dis	scussion:	25
*** *** **** **** **** ***** *********		25
8.	P-109B Contact Microphone	
Fc	our unloaded Rochelle crystals, obtained from were	25. 25
delivered to	vants to load these crystals in a different	25 25
	to a lesser degree than has done. has checked	25
the rem	horte and in denoral found them accurate and valiable	
II an sannan	corts and, in general, found them accurate and reliable.	2
However, mensitive.r	does not agree with on the point of having a highly	
sensitive, r		2
sensitive, r frequency ra reduced. not primaril	does not agree with on the point of having a highly serrow range crystal microphone. believes that the	
sensitive, r frequency ra reduced. not primaril	does not agree with on the point of having a highly barrow range crystal microphone. believes that the ange should be broader, even if sensitivity has to be prefers a frequency range from 500-2000 cps and is by concerned with filtering out any of the higher at this time.	2
sensitive, refrequency refreduced. not primarile frequencies	does not agree with on the point of having a highly narrow range crystal microphone. believes that the ange should be broader, even if sensitivity has to be prefers a frequency range from 500-2000 cps and is by concerned with filtering out any of the higher at this time. stated that the crystals must be shielded and are now	2
sensitive, refrequency refreduced. not primarile frequencies	does not agree with on the point of having a highly barrow range crystal microphone. believes that the ange should be broader, even if sensitivity has to be prefers a frequency range from 500-2000 cps and is by concerned with filtering out any of the higher at this time.	2 2 2 2
sensitive, refrequency refreduced. not primarile frequencies in the procest project.	does not agree with on the point of having a highly sarrow range crystal microphone. believes that the large should be broader, even if sensitivity has to be prefers a frequency range from 500-2000 cps and is ly concerned with filtering out any of the higher at this time. stated that the crystals must be shielded and are now eas of shielding all the microphones being used on this has come to the same conclusion and have now shielded	2 2 2
sensitive, refrequency refrequency refrequencies in the processoroject.	does not agree with on the point of having a highly sarrow range crystal microphone. believes that the ange should be broader, even if sensitivity has to be prefers a frequency range from 500-3000 cps and is by concerned with filtering out any of the higher at this time. stated that the crystals must be shielded and are now sens of shielding all the microphones being used on this has come to the same conclusion and have now shielded shones. states that this reduces the ambient noise	2 2 2 2
sensitive, refrequency refrequency remarks. not primarile frequencies in the procest project. their micropoicked up.	does not agree with on the point of having a highly harrow range crystal microphone. believes that the large should be broader, even if sensitivity has to be prefers a frequency range from 500-2000 cps and is ly concerned with filtering out any of the higher at this time. stated that the crystals must be shielded and are now eas of shielding all the microphones being used on this has come to the same conclusion and have now shielded phones. is continuing with wall and intelligibility tests.	2 2 2 2 2
requency refrequency refrequency refrequency refrequencies in the procest project. Their micropoicked up.	does not agree with on the point of having a highly sarrow range crystal microphone. believes that the ange should be broader, even if sensitivity has to be prefers a frequency range from 500-3000 cps and is by concerned with filtering out any of the higher at this time. stated that the crystals must be shielded and are now sens of shielding all the microphones being used on this has come to the same conclusion and have now shielded shones. states that this reduces the ambient noise	2 2 2 2
requency ranceduced. not primarilate frequencies in the procest project. their micropoicked up.	does not agree with on the point of having a highly narrow range crystal microphone believes that the unge should be broader, even if sensitivity has to be prefers a frequency range from 500-2000 cps and is ty concerned with filtering out any of the higher at this time. stated that the crystals must be shielded and are now eas of shielding all the microphones being used on this has come to the same conclusion and have now shielded phones states that this reduces the ambient noise is continuing with wall and intelligibility tests. Ultra-Sonic Measurement brought up the subject of wall measurement by brought up the subject of wall measurement by	2 2 2 2 2
requency range of the process of the	does not agree with on the point of having a highly harrow range crystal microphone believes that the unge should be broader, even if sensitivity has to be prefers a frequency range from 500-2000 cps and is ly concerned with filtering out any of the higher at this time. stated that the crystals must be shielded and are now eas of shielding all the microphones being used on this has come to the same conclusion and have now shielded phones states that this reduces the ambient noise is continuing with wall and intelligibility tests. Ultra-Sonic Measurement brought up the subject of wall measurement by become aware of our interest in this matter through	2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
requency ranced. not primarilar frequencies in the procest project. their micropoicked up. b. ultra-sonicat contact with scattering.	does not agree with on the point of having a highly harrow range crystal microphone believes that the unge should be broader, even if sensitivity has to be prefers a frequency range from 500-2000 cps and is ly concerned with filtering out any of the higher at this time. stated that the crystals must be shielded and are now eas of shielding all the microphones being used on this has come to the same conclusion and have now shielded shones states that this reduces the ambient noise is continuing with wall and intelligibility tests. Ultra-Sonic Measurement brought up the subject of wall measurement by is become aware of our interest in this matter through	2 2 2 2
requency refrequency refrequency refrequency refrequencies in the procession their micropolic decided up. b. contact with scattering.	does not agree with on the point of having a highly serrow range crystal microphone. believes that the large should be broader, even if sensitivity has to be prefers a frequency range from 500-2000 cps and is by concerned with filtering out any of the higher at this time. In stated that the crystals must be shielded and are now has of shielding all the microphones being used on this has come to the same conclusion and have now shielded shones. In this reduces the ambient noise is continuing with wall and intelligibility tests. Ultra-Sonic Measurement brought up the subject of wall measurement by the became aware of our interest in this matter through the work is doing on measurement by neutron backstated that he considered it feasible, to use ultra-sonic measurement instrument, instead of one based	2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
requency refrequency refrequency refrequency refrequencies in the procession their micropolic decided up. b. contact with scattering.	does not agree with on the point of having a highly serrow range crystal microphone. believes that the large should be broader, even if sensitivity has to be prefers a frequency range from 500-2000 cps and is by concerned with filtering out any of the higher at this time. In stated that the crystals must be shielded and are now has of shielding all the microphones being used on this has come to the same conclusion and have now shielded shones. It is continuing with wall and intelligibility tests. Ultra-Sonic Measurement brought up the subject of wall measurement by the become aware of our interest in this matter through the work is doing on measurement by neutron backstated that he considered it feasible, to use ultra-sonic measurement instrument, instead of one based	2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2

Declassified in Part - Sanitized Copy Approved for Release 2012/04/10 : CIA-RDP78-03172A000300050027-6

		in the second of	in the second se	
on the resonance principle signal should be at least indicated by the measurem 3 inches. Repeat measurem measurement, which should should improve with declin	50% accurate. ent is 6 inche ments could be be accurate w	s, it would be safe taken, down to the ithin 5%. Also, acc	e distance to drill final	25X1
		oposal for a quick f		25X1
on a monthly basis. within two months and wou	stated that th	e study could be com		25 X 1
This study would under Ad Hoc #25. However ultra-sonic devices and so The possibility of sting a not proven feasible and to been able to devote very proposal, in the opinion be accepted.	r, the Bureau lo far has not microwaves, as he Bureau, due little time to	come to any definite proposed by NBS, st to personnel shorta it. Therefore, the	resonant conclusions. ill has ges, has	25 X 1
		TREE / ADD		25 X ′

Distribution: P-109B - Orig. Ad Hoc #25 - 1 AWS - 1 Chrono - 1

TSS/APD/AWS/bf (2 Aug 56)

